

For new Filter Install requests: (FI)

Resident has requested that the City of Cape Coral install an irrigation filter to prevent snails from getting into the customers sprinkler system.

Resident assumes responsibility for all maintenance, cleaning, flushing of filter and any future repairs following the first year of use.

Resident has received and reviewed the Irrigation Filter Ownership/Maintenance agreement.

X _____ Date _____
(Typed Name will serve as Signature)

Property Address _____

Contact Phone _____

City will complete:

Filter Request Date

Once the electronically signed form is received by UCDInfo@capecoral.net the work will be scheduled.

For Filter Repair requests: (FR)

Resident has requested that the City of Cape Coral repair their irrigation filter.

Resident assumes responsibility for all maintenance, cleaning, flushing of filter and any future repairs.

Resident has received and reviewed the Irrigation Filter Ownership/Maintenance agreement.

X _____ Date _____
(Typed Name will serve as Signature)

Property Address _____

Contact Phone _____

City will complete:

Repair Request Date Original Install Date

Once the electronically signed form is received by UCDInfo@capecoral.net the work will be scheduled.

Irrigation Filter Ownership/Maintenance Agreement

As requested, the City of Cape Coral will install/repair your Irrigation Filter on _____ The placement of the filter will be determined by your existing system and where your control valves are. Normally, the filter is installed just before your Solenoid Control Valves, which trigger the zones on your irrigation system. ** If you have landscaping materials and plantings in the way, our staff will have to place the filter at a different location.

****The opening at the bottom is not a hose bib, using it in this manner could damage the filter. If the filter is taken apart for cleaning, do NOT tighten the bottom of the filter to much or the filter will leak.***

Flushing Procedure:

The City provides this filter for free for customers that are affected by debris in the lines. The customer is responsible for all maintenance, cleaning, flushing of filter and future repairs. Flush filter from time to time to clear any blockage. To flush all you will need to do is open the valve handle (slowly) at the bottom of the filter and flush for a few minutes to clear it. Flush once a week at first to see what your system needs. To clean cartridge, close the 1" main shut off valve. Relieve pressure by opening the ¾" flushing handle (slowly) counter clockwise, unscrew bottom bowl, remove cartridge and clean with bleach and water. Once clean put cartridge back on by reversing procedure. * NEW INSTALLS ONLY * There is a 1 year factory warranty from date of install.

If you have any questions – please call the Utilities Operations Office @ 574-0851. Thank you.